

# PRODUCT INFORMATION

## **HARDENER UT-R 20**

### **Fields of Application**

Hardener used for the adhesive solutions **CEMENT SC 2000** and **CEMENT BC 3000**.

### **Product Description**

Polymer basis:	polyisocyanate
Solvent:	dichloromethane (methylene chloride)
Colour:	brownish
Density:	1.30 g/ml
Dosage:	4% of weight of <b>CEMENT SC 2000</b> and/or <b>CEMENT BC 3000</b>
Classification:	harmful

### **Mixing**

The **HARDENER UT-R 20** is added to the respective adhesive solution and thoroughly stirred, until cement and hardener are mixed homogeneously.

### **Shelf Life**

2 years when storing in unopened original container under storing conditions in accordance with DIN 7716.

### **Available Packing Units**

Description	Contents	Product-No. Marks according to US regulations and all other countries	Product-No. Marks according to EU regulations
<b>HARDENER UT-R 20</b>	0.020 kg	525 1036	525 1036
<b>HARDENER UT-R 20</b>	0.040 kg	525 1043	525 1043

This data sheet is for informational purposes only. All data provided herein is based on in-depth research and testing, however no liability whatsoever can be assumed. Since we are constantly endeavouring to up-date and improve our products, we recommend noting the index and issue date indicated on this data sheet and to inquire as to whether any properties have changed in the interim. This Product Information Sheet replaces all prior issues. Please contact our Technical Consultant for detailed information in case of ambiguities.

TIP TOP Oberflächenschutz Elbe GmbH, Heuweg 4, D-06886 Wittenberg  
Phone: (0 34 91) 6 35 – 50, Fax: (0 34 91) 6 35 – 5 52

TIP TOP Oberflächenschutz Elbe GmbH	HARDENER UT-R 20	INDEX G of 08.10.2008
Page: 1/1	Product Information	Replaces Issue: 31.01.2008